

総称名			S50WLV			(耐塩害)			(耐重塩害)						
室内機種名			F50WLV			R50WLV			R50WLV2						
外装色 (色番号)			----- (-----)			ホワイト (5Y 7.5/1)			ホワイト (5Y 7.5/1)						
冷房能力 ★2			kW			5.0 (0.6～5.2)			別売品 パネル仕様						
暖房能力 ★3			kW			6.3 (0.5～8.6)			パネル機種名						
暖房低温能力 ★4			kW			6.2			外形寸法 H×W×D						
電源			室外電源 単相 200V 50/60Hz			外装			質量						
電気特性 ★5	運転電流	冷房	A	9.4 (最大13.8)			リモコン	機種名		ARC476A36					
		暖房	A	10.3 (最大18.0)				タイプ		ワイヤレス					
	消費電力	冷房	kW	1.790 (0.130～2.020)			コード	区分	長さ		m				
		暖房	kW	1.940 (0.120～3.000)					付属位置		個数				
	力率	冷房	%	95			標準付属品		室内	室外	パネル				
		暖房	%	94			取扱説明書		1	-----	-----				
始動電流			A	10.3			据付説明書		1	-----	-----				
補助ヒータ定格消費電力			kW	-----			保証書		1	-----	-----				
エネルギー消費効率 (COP)	冷房	冷房		2.79			リモコン		1	-----	-----				
		暖房		3.25			リモコンホルダー		1	-----	-----				
		平均		3.02			リモコンホルダー取付ネジ		2	-----	-----				
通年エネルギー消費効率 (APF) ★8			4.3			単4形アルカリ乾電池		2	-----	-----					
通年エネルギー消費効率 (APF) ★9			4.3			本体吊金具		4	-----	-----					
圧縮機種	形式		-----			断熱筒		1	-----	-----					
	機種		-----			断熱材1		1	-----	-----					
電動機出力	kW	形式		クロスフィンコイル			断熱材2		1	-----	-----				
		機種		シロッコファン			シール材		1	-----	-----				
		電動機出力×台数	W	99×1			ドレンホース		1	-----	-----				
		風量		冷:11.8 暖:13.1			ドレン継手		1	-----	-----				
ファン	風量	強 (H)	m³/min	冷:10 暖:11.8			結束バンド		6	-----	-----				
		弱 (M)	m³/min	冷:10 暖:11.8			結束バンド (固定具付き)		2	-----	-----				
		微 (L)	m³/min	冷:8.1 暖:10.7			ネジ M4X12L		4	-----	-----				
		機外静圧	Pa	-----			ドレンプラグ		-----	1	-----				
運転音 (音圧レベル) ★7	強 (H)	dB	冷:60 暖:61	冷:63 暖:65											
		dB	冷:56 暖:58	-----											
		dB	冷:51 暖:55	-----											
		dB	冷:47 暖:51	-----											
運転音 (音圧レベル) ★6	強 (H)	dB	冷:46 暖:47	冷:51 暖:53											
		dB	冷:42 暖:44	-----											
		dB	冷:37 暖:41	-----											
		dB	冷:33 暖:37	-----											
エアフィルタ			ロングライフフィルタ (パネル付属)												
製品外形寸法 (H×W×D)			mm	230×760×500			595×795×300								
梱包外形寸法 (W×D×H)			mm	989×325×624			895×368×633								
製品質量 (梱包質量)	室内	kg	14 (20)												
		標準	kg	-----			38 (42)								
		塩害	kg	-----			38 (42)								
		重塩害	kg	-----			38 (42)								
冷媒	名称	R32													
	充填量 (出荷時)	kg	0.87												
設計圧力	高圧部	MPa	4.17												
	低圧部	MPa	2.70												
冷凍機油	名称	FW68DA													
	充填量	L	0.395												
冷媒配管	標準長さ	m	5												
	最大	m	30												
	高低差	m	20												
	チャージレス長さ	m	15												
接続配管 ★10	追加充填量	15m超過時20g/m													
	液側配管	mm	φ6.4 フレア			φ6.4 フレア									
	ガス側配管	mm	φ9.5 フレア			φ9.5 フレア									
	ドレン配管		V P 2 0			V P 1 6									
冷媒配管の断熱			液・ガス断熱要												
機外配線	電源プラグ		形状番号	M4止メネジ											
	1: (㊦) 2: (㊦) 3: (㊦)		仕様	-----											
	4: (㊦) 5: (㊦) 8: (㊦)		容量	A											
	室内外連絡端子形状		3芯クイックジョイント												
室内外連絡電線 ★11 ★12			VVf φ1.6mmまたはφ2.0mm×3本												